




Connection Details of Cable Assembly



Connector sealed to IP66 only when connected to the accelerometer.

Heatshrink



Free end

Black core

White core

Screen

Materials of Cable: C01-001 PUR cable				
Pos	Description	Dimension	Overall Diameter	Remarks
1.	Tin plated copper conductor insulation of HFI 147	22 AWG 0,20	0,76 1,16	19 x 0,16 (0,34mm²)
2.	Screen wire of tin plated copper	26 AWG	0,48	19 x 0,10 (0,16mm²)
3.	Wrapped aluminium polyester foil screen		3,0	
4.	Jacket of TPU 90 M, blue pressure-extruded round	1,15	5,3 ± 0,2	

Technical Data of Cable		
Technical Data	Values at 20°C	Unit
Conductor resistance	Max: 53,1	Ω / km
Insulation resistance	> 1500	MΩ x km
Test voltage	3	KV DC
Voltage rating	600	V AC
Capacitance	Core- opposite core: 139	nF / km
	Core- adjacent core: 145	
	Core-screen: 240	
Impedance	Core- opposite core: 48	Ω
	Core- adjacent core: 44	
	Core-screen: 20	
Radiation tolerance	4 x 10 ⁴ r/s	Gy
Weight	38	g / m
Temperature rating	-40 / +90	°C
Core current rating	Max: 6	Amps at 40°C ambient air temp.